ASIL-D Safety Power Management IC for Safety Applications

FEATURES

Qualified for Automotive Applications
AEC-Q100 Qualified with the Following Results:
- Device Temperature Grade 1: -40°C to 125°C Ambient Operating Temperature Range

Wide Input Voltage Range:
- 3.0V-40V with pre-boost regulator
- 6.0V-40V without pre-boost regulator

Asynchronous Pre-Boost Controller VO_BST:
- Fixed Output Voltage of 7.5V
- Maximum Duty Cycle up to 95%
- Fixed 500kHz Switching Frequency

Synchronous Pre-Buck1 Converter VO_BUCK1:
- Fixed Output Voltage of 5.8V/5V/4V/3.3V
- Up to 1.8A Continuous Output Current
- Integrated 280mΩ High-Side and 90mΩ Low-Side Power MOSFETs
- Selectable 400kHz or 2.2MHz Switching Frequency

LDO1 VO_

SCT CONF

SCT CONF

SCT CONF

SCT CONF

SCT CO

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CO

SCT CO

SCT CON

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CO

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CO

SCT CO

SCT CONF

SCT CO

SCT CONF

SCT CO


SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CON



SCT CONF

SCT CO

SCT CONF

SCT CONF

SCT CO

SCT CONF

SCT CONF

SCT CO

SCT CONF

SCT CO

SCT CONF